

FLEXCART 48

HEADER TRANSPORT



The IDEAL tool to transport your 45ft or 50ft combine header



Why Flexcart?

- Higher capacity axles, brakes, and tires
 - Full torflex suspension
- Laminated 14" frame rails with heavily reinforced axle mounts
- Telescopic Hitch, quick adjust saddles and ratchet straps



Flexcart 48 Specifications

| | |
|--------------------|--|
| Model | Flexcart 48 |
| Dimensions (LxWxH) | 57' x 8'6" x 4' |
| Usable Deck Length | 48' |
| Weight | 5800 lb |
| GVWR | 22500lb |
| Front Axle | 6500lb Torflex |
| Rear Axles | Tandem 8000lb Torflex with electric brakes |
| Front Tires | ST235/80R16 10 ply (x2) |
| Rear Tires | ST235/80R16 14 Ply (x4) |
| Hitch | 2 5/16" Ball - 21000lb capacity |
| Optional Hitch | Pintle, Clevis |
| Lights | LED Stop/turn/tail lights |
| Safety Chains | Standard |
| Fenders | Front standard, rear optional |
| Paint | Shot blast and powder coat |
| Straps | 2 x choker style standard |
| Optional Straps | Flat hook style |

FRAME

The heavy duty frame features a pair of 4" x 14" laminated beams. The **2-piece laminated beam** increases strength and stiffness over standard structural tube.

Heavy-wall structural steel with extensive reinforcement make for a **5800lb base weight**

The frame rails and support saddles are spaced to provide solid support for the cutter bar.



HITCH

The **telescoping hitch** simplifies hook-up. Just back up close, extend the hitch as necessary to hook up, then back up slightly to re-lock the hitch.

A **21000lb capacity 2 5/16" ball** coupler with safety chains is standard.

The bolt-on style coupler allows for optional pintle or clevis type hitches.



FRONT AXLE

A **6500lb torsion stub axle** provides a smooth ride up front.

The narrow wheel spacing provides exceptional turning radius for maneuverability in tight quarters.



REAR AXLES

Tandem 8000lb axles with increased **braking capacity** and **14 ply tires** that manage the load with confidence

Full **torflex suspension** offers a smooth ride and low maintenance.

The axle mounts are heavily reinforced to **maintain wheel alignment** and prolong tire life.

Electric brakes are standard on both rear axles.



SUPPORT AND TIE-DOWN

Adjustable support saddles and ratchet strap can be quickly positioned to match your header.

The support saddles are **lined with UHMW plastic** to help protect your paint.

Both **flat hook and choker style straps** are available to suit your needs.



BRIDGEVIEW 
www.bridgeviewmanufacturing.com
PH: 306-745-2711 FAX: 306-745-3364
Box 4 Hwy 22 Gerald, SK, S0A 1B0